

www.forzaups.com

Forza's NT series is designed to provide electric protection for your personal computer and peripherals. Featuring a compact design, the unit is ideal for small work spaces at the office or at home. Although small in size, it provides the maximum protection against the constant threat of electrical supply outages.



FEATURES

- Uninterruptible power system for home and office equipment
- Automatic voltage regulator
- Power surge and spike protection
- Phone, fax and modem protection
- (4) outlets with battery back up and AVR protection
- Two year full warranty







MODEL		NT-1002U
CAPACITY		1000VA/500W
INPUT	Nominal voltage	220V
	Voltage range	162-268VCA
	Frequency	50/60Hz (autosensing)
	AC plug style	1 NEMA 5-15P
ОИТРИТ	Nominal voltage	220V +/- 10%
	Frequency	50/60Hz
	Frequency stability	+/- 1Hz battery mode
	Waveform	Modified sine wave
	Total outlets	4 (NEMA 5-15R)
	Full battery / Surge protection outlets	4
	Surge protection outlets only	0
	Phone/Modem/Fax protection	RJ-11
BATTERY	Type and quantity	12V 9Ah (1)
	Backup time	25 min.
	Recharge time	6 hours to 90% after complete discharge
VOLTAGE REGULATION	Voltage regulation (120/220V)	220V
VOLINGE REGUENTION	Boost feature (120/220V)	Vin x 1.18
	Buck feature (120/220V)	Vin x 0.85
FREQUENCY REGULATION	Automatic frequency selection	Yes
LINE/BATTERY TRANSFER	Typical transfer time	2-6ms
	Low line transfer to battery (120/220V)	162VAC
	High line transfer to battery (120/220V)	268VAC
ALARMS/INDICATORS	Visual indicators	AC mode: solid blue
		Battery mode: flashing blue
		Fault mode: blue light goes out
	Audible	Battery mode: sounds every 10 seconds
		Low battery: Sounds every second
		Overload: sounds every 0.5 second
		Fault: continuous sound
PROTECTION	Full protection	Line mode: 110%+20%/-10%; shutdown after 5 minutes and go to fault mode.
	. ,	120%+20%/-10%; shutdown immediately and go to fault mode.
		Battery mode:120%+20%/-10%; shutdown immediately
	Joules	200J
SPECIAL FEATURES	"Cold start" option	Yes
	Auto charge	Yes
ENVIRONMENT	Operating temperature	32-104° F
	Storage temperature	5-113° F
	Relative humidity	0-90% non-condensing
	Audible noise	<40 dB at one meter
PHYSICAL APPEARANCE	Power switch	Yes (Lighted)
	Housing	ABS Plastic (Flame retardant)
	Color	Black
	Cord length	3ft
	Product dimensions	11 x 4 x 5.6in
	Product weight	10.81b
ADDITIONAL INFORMATION	Warranty	2 Years
	Package content	UPS, User guide
	Box dimensions	12.8 x 5.5 x 8.7in
	Box weight	11.47lb
	UPC	7.98302E+11













