

## www.forzaups.com

Forza's **NT** series is designed to provide electric protection for your personal computer and peripherals. With its compact size, the unit is ideal for small work spaces at the office or at home. Although small in size, it provides the maximum protection against the constant threat of electrical supply outages.



## **FEATURES**

- Uninterruptible power system
- Power protection for home and office equipment
- Automatic voltage regulator
- Boost & buck AVR to stabilize voltage
- 4 outlets with battery back up and AVR protection
- Phone, Fax & modem protection (RJ-11)
- Two year full warranty







MODEL		NT-761D
CAPACITY		750VA/375W
INPUT	Nominal voltage	120V
	Voltage range	89-145VAC
	Frequency	40Hz - ∞ (autosensing)
	AC plug style	1 NEMA 5-15P
ОИТРИТ	Nominal voltage	120V +/- 10%
	Frequency	40Hz - ∞
	Frequency stability	+/- 1Hz battery mode
	Waveform	Modified Sine Wave
	Total outlets	4 (NEMA 5-15R)
	Full battery / Surge protection outlets	5
	Surge protection outlets only	0
	Phone/Modem/Fax protection	RJ-11
BATTERY	Type and quantity	12V 4.5Ah (1)
	Backup time	18 min.
	Recharge time	6 hours to 90% after complete discharge
VOLTAGE REGULATION	Voltage regulation (120/220V)	120V
	Boost feature (120/220V)	Vin x 1.18
	Buck feature (120/220V)	Vin x 0.85
FREQUENCY REGULATION	Automatic frequency selection	Yes
LINE/BATTERY TRANSFER	Typical transfer time	2-6ms
	Low line transfer to battery (120/220V)	89VAC
	High line transfer to battery (120/220V)	145VAC
ALARMS/INDICATORS	Visual indicators	AC mode: solid blue
		Battery mode: flashing blue
		Fault mode: blue light goes out
	Audible	Battery mode: sounds every 10 seconds
		Low battery: Sounds every second
		Overload: sounds every 0.5 second
		Fault: continuous sound
PROTECTION	Full protection	Line mode: 110%+20%/-10%; shutdown after 5 minutes and go to fault mode.
		120%+20%/-10%; shutdown immediately and go to fault mode.
		Battery mode:120%+20%/-10%; shutdown immediately
	Joules	200J
SPECIAL FEATURES	"Cold start" option	Yes
	Auto charge	Yes
ENVIRONMENT	Operating temperature	32-104° F
	Storage temperature	5-113° F
	Relative humidity	0-90% non-condensing
	Audible noise	<40 dB at one meter
PHYSICAL APPEARANCE	Power switch	Yes (Lighted)
	Housing	ABS Plastic (Flame retardant)
	Color	Black
	Cord length	3ft
	Product dimensions	11 x 4 x 5.6in
ADDITIONAL INFORMATION	Product weight	10.6lb 2 Years
ADDITIONAL INFORMATION	Warranty	
	Package content	UPS, User guide
	Box dimensions	12.8 x 5.5 x 8.7in 8.2lb
	Box weight UPC	8.2ID 7.98302E+11
	UPC	7.703UZETT1













