forzaups.com



NT-511

Forza's NT series is designed to provide electric protection for your personal computer and peripherals.



With its compact size, the unit is ideal for small work spaces at the office or at home. Although small in size, it provides the maximum protection against the constant threat of electrical supply outages.

Highlights

- Uninterruptible power system
- Power protection for home and office equipment
- Boost and buck AVR to stabilize voltage
- 6 outlets with battery back up and AVR protection
- Phone, fax & modem protection (RJ-11)
- Three-year warranty





+ Breaker + Surge Protector + Voltage Protector + Voltage Regulator + Power Back up

| MPN | NT-511 |
|--|--|
| General | |
| Capacity | 500VA/250W |
| Input | |
| Nominal voltage | 120V |
| Voltage range | 89-145VAC |
| Frequency | 45-65Hz |
| | (autosensing) |
| AC plug style | NEMA 5-15P |
| Output | |
| Nominal voltage | 120V +/- 10% |
| Frequency | 50/60Hz |
| Frequency stability | +/- 1Hz battery mode |
| Waveform | Modified sine wave |
| Total outlets | 6 (NEMA 5-15R) |
| Full battery / Surge protection outlets | 4 |
| Surge protection only outlet | 2 |
| Phone/modem/fax protection | RJ-11 |
| Battery | |
| Battery type and quantity | 12V 4.5Ah (1) |
| Backup time | 18 min* |
| Recharge time | 6 hours to 90% after complete discharge |
| Voltage regulation | |
| Voltage regulation (120/220V) | 120V |
| Boost feature (120/220V) | Vin x 1.18 |
| Buck feature (120/220V) | Vin x 0.85 |
| Frequency regulation | |
| Automatic frequency selection | Yes |
| Line/Battery transfer | |
| Typical transfer time | 2-4ms |
| Low line transfer to battery (120/220V) | 89VAC |
| High line transfer to battery (120/220V) | 145VAC |
| Alarms/Indicators | |
| Visual indicators | AC mode: solid blue |
| | Battery mode: flashing blue |
| | Fault mode: blue light goes out |
| | Battery mode: sounds every 10 seconds |
| Audible | Low battery: sounds every second |
| | Overload: sounds every 0.5 second |
| | Fault: continuous sound |
| Protection | Fault. Continuous sound |
| Full protection | |
| rui protection | Line mode: 110%+20%/-10%; shutdown after 5 minutes and go to fault mode. 120%+20%/-10%; shutdown immediately and go to fault |
| | mode. Battery mode: 120%+20%/-10%; shutdown immediately |
| Joules | 200J |
| Special features | |
| "Cold start" option | Yes |
| Auto charge | Yes |
| Environment | |
| Operating temperature | 32-104° F |
| Storage temperature | 5-113° F |
| Relative humidity | 0-90% non-condensing |
| Audible noise | <40 dB at one meter |

| MPN | NT-511 |
|------------------------|-------------------------|
| Physical appearance | |
| Power switch | Yes (lighted) |
| Housing | Flame retardant plastic |
| Color | Black |
| Cord length | 3ft |
| Dimensions | 11x4x5.6in |
| Weight | 10.lb |
| Additional information | |
| Warranty | 3 years** |

* Calculated with a single PC plus monitor ** Limited to 2 years on batteries

