

## NT-1002A

Forza's NT series is designed to provide electric protection for your personal computer and peripherals.



With its compact size, the unit is ideal for small work spaces at the office or at home. Although small in size, it provides the maximum protection against the constant threat of electrical supply outages.

### Highlights

- Uninterruptible power system
- Power protection for home and office equipment
- Automatic voltage regulator
- Boost and buck AVR to stabilize voltage
- 4 outlets to protect your devices
- RJ45/11 network, internet and phone line surge protection
- Three-year warranty



Ideal for



**1000VA**

**PROTECTION LEVEL 5**

- + Breaker
- + Surge Protector
- + Voltage Protector
- + Voltage Regulator
- + Power Back up

MPN	NT-1002A
<b>General</b>	
Capacity	1000VA/500W
<b>Input</b>	
Nominal voltage	220V
Voltage range	162-268VAC
Frequency	45-65Hz (autosensing)
AC plug style	Argentina Type I
<b>Output</b>	
Nominal voltage	220V +/- 10%
Frequency	50/60Hz
Frequency stability	+/- 1Hz battery mode
Waveform	Modified sine wave
Total outlets	4 (Argentina Type I)
Full battery / Surge protection outlets	4
Network protection	RJ-45
Phone/modem/fax protection	RJ-11
<b>Battery</b>	
Battery type and quantity	12V/9Ah (1)
Backup time	32min**
Recharge time	4 hours to 90% after complete discharge
<b>Voltage regulation</b>	
High cutoff	268VAC +/- 5%
Boost 1	162-204V +/- 5%
Buck	236-268V +/- 5%
Low cutoff	162VAC +/- 5%
<b>Frequency regulation</b>	
Automatic frequency selection	Included
<b>Line/Battery transfer</b>	
Typical transfer time	2-4ms
Low line transfer to battery	162VAC +/- 5%
High line transfer to battery	268VAC +/- 5%
<b>Alarms/Indicators</b>	
Visual indicators	AC mode: solid blue Battery mode: blinking blue Fault mode: blue light goes out
Audible	Battery mode: sounds every 10 seconds Low battery: sounds every second Overload: sounds every 0.5 second Fault: continuous sound
<b>Protection</b>	
Full protection	Voltage regulation, overload, discharge and overcharge protection
Joules	200J
<b>Special features</b>	
"Cold start" option	Included
Auto charge	Included
<b>Environment</b>	
Operating temperature	32-104°F
Storage temperature	-4-122°F
Relative humidity	0-90% non-condensing
Audible noise	<40dB at one meter

MPN	NT-1002A
<b>Physical appearance</b>	
Power switch	Push button
Housing	ABS fire retardant plastic
Color	Black
Dimensions	11x4x5.6in
Weight	10.8lb
<b>Additional information</b>	
Warranty	3 years*

\*\*Single PC plus monitor  
\*2 years on batteries

