

The smart line of Forza, the new SL series, is certainly the complete UPS solution for government agencies or private businesses, in the educational, financing and public sectors, as well as for small and medium-sized companies. By integrating voltage regulation, surge suppression and back-up capabilities in a single unit, along with critical protection and power management features, the new SL series is sure to become the best selling UPS of its class, for its quality and outstanding performance. The new SL includes a power management software, with the latest in system monitoring technology.



## **FEATURES**

- 6 NEMA 5-15R battery backup outlets
- 2 NEMA 5-15R surge protection outlets
- Complete AVR protection
- LED indicators let you know the device is on, the battery status and AC mode
- Available USB and RJ11 protection for your Internet/Phone/Fax/Modem
- An illuminated Power Button
- Comes with proprietary ForzaTracker monitoring software and Norton Internet Security, 90-day trial
- USB Cable included
- 2 year full warranty

## **STANDARD APPLICATIONS**

- TVs
- CD/DVD players
- Computers
- Printers
- Game consoles
- Home theaters



CONNECTIONS		<i>5L-1001UL</i>
	Input	
	Output	



MODEL	FEATURES	SL-1001UL
CAPACITY		1000VA/600W
	Input voltage compatibility	110/120VAC
INPUT	Input voltage range	89-145VAC
	Frequency	45-65Hz (auto sensing)
	Output Nominal voltage	110/120VAC
OUTPUT	Output voltage regulation (Batt. Mode)	±10%
OUTPUT	Output frequency	50/60Hz
	Output waveform	Modified sine wave
BATTERY	Back-up time (at a PC load with 17" monitor)	40 minutes
	AC Mode	Power Button: Blue LED Light
INDICATOR	Battery mode	Power Button Blue LED Light Green flashing light The 1st to 4th Blue LED light gradually indicates battery capacity
	Fault mode	Power button: Blue LED light; Red LED below power button
	Battery mode	Sounding every 10 seconds
	Low battery	Sounding every 1 second
AUDIBLE ALARM	Overload	Sounding every 0.5 seconds
	Battery replacement	Sounding every 2 seconds
	Fault	Continuous sounding
PROTECTION	Full protection	Line Mode: 110%+20%/-10%; shutdown after 5 minutes and go to fault mode. 120%+20%/-10%; shutdown immediately and go to fault mode. Battery Mode:110%+20/-10%; shutdown after 5 sec. 120%+20%/-10%; shutdown immediately
	Joules	660J
	Unit dimension, DXWXH (mm)	392*145*205
PHYSICAL	Unit dimension, DXWXH (in)	15.4*5.7*8.1
APPEARANCE	Net unit Weight (kgs/lbs)	9.8kg
	Packing dimensions (mm)	490*230*292
		19.29*9.06*11.5















